Historic, archived document

Do not assume content reflects current scientific knowledge, policies, or practices.



CONSTRUCTION


HINTS


UNITED STATES DEPARTMENT OF AGRICULTURE, FOREST SERVICE WASHINGTON, D.C.

Vol. 2

October 3, 1936


No, 18







Where difficulty is encountered due to the upholstery tearing loose in truck cabs, a clip may be made of light gauge sheet metal (tobacco tins or discarded cans have been found satisfactory). The clip may be slipped over the guimp and beneath the side material, and tacked into place. With a light dab of matching paint, it is hardly noticeable.

Submitted by P. F. Friedman, Sup., Camp No. S-106, Salamanca, N. Y.








NOTE

Locing and Ties to be 3/16 high grade Sosh Cord Ties to hove 12" of loose cord. All Grommets to be bross with 1/2" holes and spaced 6" o.c. and 1/2 from edge except as noted.

ALLEGHENY NATIONAL FORES DESIGN OF TOP CANOP DUMP BODY TRUCK Scole #=/ June 193



DUMP TRUCK TOPS

6 pcs /x2"x3' Fin. Size Clear Straight Grained Oak 1pc. 1"x2"x8" 545 Clear Straight Grained Ook

- 3 Structural Steel Bows as shown
- 3 \$ x / Flot Head Stove Bolts
- 3 Wrought Iron Washers for a 3 Bolt
- 18 4 x 2" Flot Head Stove Bolts
- 18 Wrought Iron Washers for 4 Bolts
- 12 12-2" Flat Head Wood Screws

SHORT WHEEL-BASE STAKE TRUCK TOPS

2 pcs. 2"x4"x10 545 Clear Ash

2 pcs. 2x4x7'545 Clear Ash

8 pcs. 2"x4"x4" 545 Cleor Ash

1 pc. 1" x2"x 10'545 59.E. \$5. Oak

2 pcs. 1"x 12"x10" 545 *1 Com. V.P. 20 *10-12" Flat Head Wood Screws

32 #10-2 Flat Head Wood Screws

4 - 2 x2" Str. Steel Bows

4 - 5td. 4"x4" Heavy Wrought

Steel Corner Brackets

4 & 6"x6"x 3" x 32" Std. Angle

24 - 4x22 Flat Head 5. Bolts

4 \$ x 13 Flot Head S. Bolts

44- 3 x 24 R. Head S. Bolts

24 5 Wrought Iron Woshers

50 7 Wrought Iron Washers

LONG WHEEL-BASE STAKE TRUCK TOPS

2 pcs. 2"x4"x12' S45 Clear Ash

2 pcs. 2"x4"x7 545 Clear Ash

10 pcs. 2"x4"x4' S45 Clear Ash

1 pc. 1"x2"x12'545 Sq.E. \$5. Oak

2 pcs. 1"x12"x12"545 #1 Com. Y.P.

30 % Wrought Iron Washers

60 To Wrought Iron Washers

40 # 10-2" Flot Head Wood Screws

20 # 10-12" Flat Head Wood Screws

5 Zx2" Str. Steel Bows

4 Std. 4"x4" Heavy Wrought

Steel Corner Brockets 4 15 6"x6"x16x32" Std Angle

30 \$ x2 = Flat Head S. Bolts

5 & x 13" Flat Head S. Bolts

52 3"x 24 Round Head S. Bolt

ALLEGHENY NATIONAL FOREST DESIGN OF TOP FRAMES MATERIAL LISTS July 1936

CAT11086622_035 Construction hints 1.9 F76Ch v.2:no.18 1936

Batch: NAL17_0080